



BISON Innovative Products


Get CEU Credits, Details, & Specifications online at www.bisonip.com

701 Osage Street, Unit 120, Denver, CO 80204 USA
Phone 303.892.0400 Toll Free 800.333.4234 Fax 303.825.5988
EMail info@bisonip.com Web www.bisonip.com


LEVEL.IT
Adjustable Pedestals




VT18 / VT316
1/8" FIXED HEIGHT
(3mm)




HD25-18 / HD25-316
1/4" FIXED HEIGHT
(6mm)




HD50-18 / HD50-316
1/2" FIXED HEIGHT
(13mm)




HD75-18 / HD75-316
3/4" FIXED HEIGHT
(19mm)




LO-18 / LO-316
1 1/4" - 2" VERTICAL RANGE
(32mm - 51mm)




LC-18 / LC-316
2" - 4 3/4" VERTICAL RANGE
(51mm - 121mm)



LC + C1
4 3/4" - 6 1/4" VERTICAL RANGE
(121mm - 159mm)



LC + C4
6 1/4" - 8 3/4" VERTICAL RANGE
(159mm - 222mm)




LC + C4 + C4
8 3/4" - 12" VERTICAL RANGE
(222mm - 305mm)

PRODUCT CHARACTERISTICS

- MAXIMUM DESIGN CAPACITY OF **750** LBS PER PEDESTAL, FACTOR OF SAFETY 3.
- SCREW ADJUSTABILITY WHILE PEDESTALS ARE LOADED FOR FINAL ADJUSTMENT.
- IMPERVIOUS TO FREEZE-THAW, WATER, MOLD AND SOLVENT FREE CHEMICALS.
- SCORED BASE ALLOWS SUPPORTS TO BE TRIMMED FOR TIGHT AREAS.
- WEIGHT BEARING SYSTEM DOES NOT PENETRATE ROOFING MEMBRANE OR SUBSTRATE.
- LARGE FOOTPRINT SPREADS WEIGHT OVER ROOFING MEMBRANE AND SUBSTRATE.
- MAXIMUM CAVITY HEIGHT 12".

GENERAL NOTES: APPLY TO ALL OF THE ABOVE PRODUCTS

1. INSTALLATION MUST BE COMPLETED IN ACCORDANCE WITH BISON INNOVATIVE PRODUCTS SPECIFICATIONS.
2. DRAWINGS NOT TO SCALE.
3. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.BisonIP.com



PEDESTAL ELEVATIONS

ELEVATIONS FROM 1/8" TO 12"